



China 608z Bearing Supplier



6307 Bearing 2D drawings and 3D CAD models

Kent Bearing Factory Use in Machine Bearing
 6307 6308 6309 6310 6311 6312 6313 6314 6315 RS
 Rz Zz NSK NACHI NTN Koyo Timken SKF
 Bearings

Bearing No. 6307

Size	35x80x21 mm
Bore Diameter	35 mm
Outer Diameter	80 mm
Width	21 mm
d	35 mm
D	80 mm
B	21 mm
C	21 mm
r min.	1.5 mm
da min.	44 mm
Da max.	71 mm
ra max.	1.5 mm
Weight	0.457 Kg
Basic dynamic load rating (C)	33,5 kN
Basic static load rating (C0)	19,2 kN
(Grease) Lubrication Speed	8400 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	3.02
Product Group	B00308
Enclosure	Open



China 608z Bearing Supplier

Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	35MM Bore; 80MM Outside Diameter; 21MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Outside Diameter	3.15 Inch 80 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.378 Inch 35 Millimeter
Outer Race Width	0.827 Inch 21 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	35 mm
Width	21 mm
Fillet Radius/Chamfer	1.5 mm



China 608z Bearing Supplier

Dynamic Load Rating	33,500 N
Static Load Rating	19,200 N
Limiting Speed - Grease	8,800 rpm
Limiting Speed - Oil	10,000 rpm
Factor f_0	13.2
Radial Clearance	0.006 to 0.020 mm
da (min)	44 mm
Da (max)	71 mm
ra (max)	1.5 mm